ILS Synergy DT-series Presenter lecterns

Synergy DT uses the same Universal Mounting System techniques that make the Synergy series lecterns so versatile. Cradle your all-in-one touch PC in your lectern, and use the folding stand to provide you with an optimal reading angle. **Synergy DT** has been specially designed to hold a Dell 7000 Series and Lenovo all-in-one PCs, and supports 23"-24"-27" high and ultra high resolution monitors on a heightand angle adjustable arm for great flexibility.

Dimensions

Width	No side plates: 20cm pillar, 70cm top With side plates: 140cm top side plate size: 36cm x 26cm
Height	User side min: 80cm, max: 120cm Audience side min: 94cm, max: 134cm
Weight	60kg
	Integration
Computer support	Display is integrated into computer - All In One Base is clamped into the lectern. Display wooden surface option to cover the display. All In One Touch PCs compatibale: Dell Inspiron 24" 7459 Lenovo 27" AIO A740, new Lenovo 27" AIO A910
Audio	1 x shock mount XLR socket 1 x regular mount XLR-3 pin Socket for microphone (or 1 x regular mount XLR-4 pin for the reading light) Optional 4 speakers integrated into the top with 280W amplifier.

Connectivity

Side connectivity panel	Laptop connectivity: HDMI, DP, VGA and 3.5 Audio, Ethernet Integrated computer expansion ports: 2 x USB Sockets for external USB devices
Top dashboard	8" wide tablet holder for control panels and tablets with integrated Apple Lightning and/or Micro USB charging plugs Integrated computer expansion ports: 2 x USB Sockets for external USB devices 25:00 Start Reset
D. II.	Second display and a UDAN of interested assessed

Bottom cabling

Second display connection HDMI of integrated computer HDMI, DP, VGA and 3.5 Audio cables from connectivity side panel or integrated 4x1 HDMI switcher with only one HDMI/CAT6 cable in the bottom. Ethernet, Power,

Microphone output: XLR cable per microphone

