



Width	No side plates: 42cm pillar, 70cm top With side plates: 156cm top Side plate size: 36cm x 29cm				No side plates: 20cm pillar, 70cm top With side plates: 140cm top Side plate size: 36cm x 26cm		
Height	User side min: 94cm, max: 120cm Audience side min: 114cm, max: 140cm casters add 7cm				User side min: 80cm, max: 120cm Audience side min: 94cm, max: 134cm		
Weight	75kg	75kg	68kg	70kg	65kg	60kg	60kg
Display & PC	29" 21:9 IPS Display 12" Touch Keyboard	All In One Touch-PC compatible*:	VESA mount monitor* Space for mini-PC *	Place you laptop on top surface or sideplates.	All In One Touch-PC compatible*:	VESA mount monitor* Space for mini-PC *	Place you laptop on top surface or sideplates.
	Configurable industrial Mini-ITX motherboard with latest Intel® processor	Popular configurations: Dell Inspiron 24" 7459 Lenovo 27" AIO A910 Tilt adjustable mechanism of the PC. <i>* Base is clamped into the lectern Display wooden surface option to cover the display.</i>	Popular configurations: Wacom 2240/2241 or ViewSonic Pen/Touch Monitor mini-PC: Giada i59u *Custom configuration possible	Wooden top surface Size: 70 x 45 Handrails covered	Popular configurations: Dell Inspiron 24" 7459 Lenovo 27" AIO A910 Tilt adjustable mechanism of the PC. <i>* Base is clamped into the lectern Display wooden surface option to cover the display.</i>	Popular configurations: Wacom 2240/2241 or ViewSonic Pen/Touch Monitor mini-PC: Giada i59u *Custom configuration possible	Wooden top surface Size: 45 x 50 Handrails opened
Audio	Optional 4 speakers integrated into the top with 280W amplifier. 1 x shock mount XLR socket 1 x regular mount XLR-3 pin Socket for microphone or 1 x regular mount XLR-4 pin for the reading light						
Side connectivity panel	HDMI, DP, VGA and 3.5 Audio, Ethernet Integrated computer expansion ports: 2 x USB Sockets for external USB devices						
Top dashboard	8" wide tablet holder for control panels and tablets with integrated Apple Lightning and/or Micro USB charging plugs Integrated computer expansion ports: 2 x USB Sockets for external USB devices						
Bottom cabling	Second display connection HDMI of integrated computer. HDMI, DP, VGA and 3.5 Audio cables from connectivity side panel or integrated 4x1 HDMI switcher with only one HDMI/CAT6 cable in the bottom. Ethernet, Power, Microphone output: XLR cable per microphone						