

Date:		REF Number:	
Model:		QTY:	
Contact:			

1. TOP SURFACE

- ☐ **Aluminium Plate** (Smooth top working surface, without possibility of monitor installation)
- ☐ **Wood plate** (Smooth top working surface, without possibility of monitor installation)
- ☐ ***VESA mount** (Only for: monitor / AIO PC installation)
- ☐ ***Articulating Stand** (Only for: monitor / AIO PC installation)
- ☐ ***Monitor** (max 24") **with extra space to the right** for control panel, laptop or notes (only for **QW** and **UW** series)

***MONITOR**

- ☐ Included **by ILS** (model) _____
- ☐ Included **by CUSTOMER** (model) _____
- ☐ **NOT** included

***COMPUTER / AIO PC**

- ☐ Included **by ILS** (model) _____
- ☐ Included **by CUSTOMER** (model) _____
- ☐ **NOT** included

***CONTROL / TOUCH PANEL**

- ☐ Included **by ILS** (model) _____
- ☐ Included **by CUSTOMER** (model) _____
- ☐ **NOT** included

***OTHER DEVICES**

- ☐ Included **by ILS** (model) _____
- ☐ Included **by CUSTOMER** (model) _____
- ☐ **NOT** included

2. CONNECTIONS ON THE FRONT PANEL OF THE TOP

- ☐ NONE
- ☐ 3-Pin XLR anti-shock mount for the microphone
 - ☐ - 1 ☐ **Left** side of the top from the user perspective ☐ **Right** side of the top from the user perspective
 - ☐ - 2
- ☐ BNC Light socket (12V)
 - ☐ **Left** side of the top from the user perspective ☐ **Right** side of the top from the user perspective
- ☐ 2x USB 3.0 (by default)

YOUR REQUEST: _____

3. ACCESSORIES

- ☐ NONE
- ☐ Head Tilt mechanism
- ☐ Gooseneck condenser microphone AKG CGN 99 c/s
 - ☐ - 1 ☐ - 2
- ☐ T-bone GM5212 microphone
 - ☐ - 1 ☐ - 2
- ☐ Light – LITTLITE LED BNC lamp
- ☐ Light – ADAM HALL BNC lamp

YOUR REQUEST: _____

4. CONNECTIONS ON THE SIDE PANEL OF THE TOP

- | | |
|-------------------------------|--|
| <input type="checkbox"/> NONE | <input type="checkbox"/> *Right (from the user perspective) |
|-------------------------------|--|

***Connections:**

- ☐ AC Power Socket (☐ -1 ☐ -2)
- ☐ Cutout for mini-PC

***Connections:**

- ☐ AC Power Socket (☐ -1 ☐ -2)
- ☐ Cutout for mini-PC

☐ Panel with Custom Sockets (**4 max per one side**):

SOCKET:	QTY:
HDMI	
LAN	
VGA	
mini DP	
USB 3.0 -A	
USB 3.0 -B	
USB Type – C	
3.5mm Audio	

☐ Panel with Custom Sockets (**4 max per one side**)

SOCKET:	QTY:
HDMI	
LAN	
VGA	
mini DP	
USB 3.0 -A	
USB 3.0 -B	
USB Type – C	
3.5mm Audio	

YOUR REQUEST: _____

5. **ADDITIONAL BUTTONS ON THE FRONT PANEL OF THE TOP**

- ☐ Up & Down height control (**by default**, if the lectern has a height adjustment)
☐ Head tilt control (**by default**, if the lectern has a head tilt)
☐ Mute ON/OFF
☐ Light ON/OFF

YOUR REQUEST: _____

6. **SIDE TABLES**

Fixed detachable side tables (450mm x 295mm)

- ☐ NONE
☐ **FIXED** detachable side tables (**two** are possible) ☐ **SLIDING** side table (**only one** is possible)
☐ Left ☐ Right ☐ Left ☐ Right

7. **KEYBOARD TRAY**

- ☐ **Small sliding out** Keyboard Tray (430 mm x 180 mm)
☐ **Large sliding out** Keyboard Tray with space for a mouse (705 mm x 270 mm)
☐ NO

8. **LOGO ENGRAVING** (on the fixed **front panel** of the Wide Pillar – 285 mm x 700 mm)

- ☐ YES
☐ NO

9. **EXTRAS**

- ☐ **Head Tilt** mechanism (adds extra **12°** tilt adjustment to the head mounted on fixed 12° surface)
☐ **Expansion Box** for extra equipment (w:335mm x h:635mm d:70mm) – Is attached to the wide pillar from the user side)

10. **CONNECTIONS ON THE BOTTOM** (Depends on the integration of equipment)

CONNECTION:	QTY:
Power cable for a system (<input type="checkbox"/> US <input type="checkbox"/> UK <input type="checkbox"/> EU <input type="checkbox"/> Other _____)	
XLR Cable	
HDMI	
CAT5e (LAN,Control)	
CAT6a (HDBaseT)	
USB 3.0 Type A (male)	
3.5mm Audio	
VGA	

YOUR REQUEST: _____

YOUR NOTES: _____

