

# ILS lecterns comparison sheet

on height adjustable pillar



	ILS11A	ILS12X	ILS15V	ILS21H	ILS25V	ILS27D	ILS22M
<b>description</b>	Laptop i/f only	choose a VESA mountable monitor/bundle with mini PC	choose a VESA mountable monitor/touchPC with top plate and side for connectivity, XLRs	ILS integrated PC and touch monitor with laptop switcher	external touchPC or monitor&PC integration on VESA mountable platform and wide pillar	external touchPC integration using the touchPC's own stand on wide pillar	ILS integrated PC and all covering PCT touch glass incl. control system
<b>height-adjustable</b>	yes	yes	yes	yes	yes	yes	yes
<b>adjustment range</b>	20 cm	35 cm	35 cm	35 cm	20 cm	20 cm+monitor tilt lift stand	35 cm
<b>monitor size</b>	-	any 5 - 32"	any 5 - 32"	21.5"	any 5 - 32"	21.5" - 27"	21.5"+31" touch
<b>monitor resolution</b>	-	choice monitor	choice monitor, wood&acrylic plates	HD (1920x1080)	HD and up	HD and up	HD (1920x1080)
<b>desk size</b>	58 cm x 42 cm	choice monitor dimension	70 cm wide	77 cm x 40 cm	70 cm wide	70 cm wide	65 cm x 50 cm
<b>side tables</b>	yes 22x33 cm	yes 30x45 cm	yes	yes 22x33 cm	yes	yes	yes 22x33 cm
<b>touch method</b>	-	pen or touch	pen or touch	touch	pen or multi-touch	multi-touch	multi-touch
<b>touchPC</b>	-	HP Touchsmart, DELL One, Lenovo Horizon, Crestron V24	HP Touchsmart, DELL One, Lenovo Horizon	ILS	HP Touchsmart, DELL One, XPS, Lenovo Horizon, Crestron V24	DELL One 2350/7000 series and Lenovo A740	ILS
<b>monitor</b>	-	WACOM 2241, 2242, SMART SP518, SP524, Viewsonic TD2220, Sharp K322B, ILS2200P	WACOM 2241, 2242, SMART SP518, SP524, Viewsonic TD2220, Sharp K322B, ILS2200D	-	WACOM 2241, 2242, SMART SP518, SP524, Viewsonic TD2220, Sharp K322B, ILS2200D	-	-
<b>control I/O</b>	-	-	option, default smartphone stand	-	option, default smartphone stand	option, default smartphone stand	11 relays, 4 RS232
<b>power socket</b>	yes	no	yes with side table	no	yes with side table	yes with side table	no
<b>mic XLR socket</b>	1	option for 1	1 (or 2 with no light)	1	1 (or 2 with no light)	1 (or 2 with no light)	1 (or 2 with no light)
<b>light socket</b>	1	-	1	1	1	1	1
<b>internal PC spec</b>	-	optional: i5-4200U, 8GB RAM, 128GB SSD, 500GB HDD	optional: i5-4200U, 8GB RAM, 128GB SSD, 500GB HDD	i5-4240, 4GB RAM, 320 GB HDD, DVD	vendor specific	vendor specific	i5-4250U, 8GB RM, 256GB SSD, BD
<b>signal i/f</b>	VGA/LAN/XLR/jack	VGA/HDMI in top pillar	HDMI/VGA/USB/LA N/XLR/jack	HDMI/VGA/USB/LA N/XLR/jack+ VGA/audio notebook	HDMI/VGA/USB/LA N/XLR/jack	HDMI in+out, 2nd HDMI	DP/VGA/HDMI/ 2LAN/USB
<b>switcher built in</b>	-	-	optional 3 way HDMI	2x1 VGA	optional 3 way HDMI	optional 3 way HDMI	control system built in
<b>keyboard</b>	-	keyboard holder with microphone stand	place on side table	place on side table	place on side table	place on side table	integrated under touch glass
<b>default pedestal</b>	narrow aluminum power lift at 12°	narrow aluminum power lift at 12°	narrow aluminum power lift at 12°	narrow aluminum power lift at 12°	wide aluminum lift straight up	wide aluminum lift straight up	narrow aluminum power lift at 12°
<b>alternatives</b>	ILS11W	ILS11AA	ILS14iD		ILS25G	ILS27L	
	wooden top	integrated speaker array in top and sub woofer in base	With Lenovo 21.5" Edge touchPC plus 3.5" touch panel AMX/Crestron		acrylic insert replacing monitor or touchPC inserts	With Lenovo 27" ideacentre A740	
<b>options</b>	microphone	microphone	microphone	microphone	microphone	microphone	microphone
	reading light	reading light	reading light	reading light	reading light	reading light	reading light
	audio	audio	audio	audio	audio	audio	audio
	switchers	switchers	switchers	switchers	switchers	switchers	switchers
	control systems	control systems	control systems	control systems	control systems	control systems	control systems
		podium cabinet replacing pillar			podium cabinet replacing pillar	podium cabinet replacing pillar	